

**Assembly-, gas fill- and
press robots
Types ZPG-R**

Gas filling of rectangular and shaped formats at highest level

- ◆ Automatic assembling and pressing of insulating glass units, optional with gas filling
- ◆ Slip free glass plate transport via servo controlled belt conveyor
- ◆ Optimized gas filling for rectangular and shaped formats
- ◆ Gas filling times independent of the length of the insulating glass units
- ◆ Adjustable, precise press plate guiding
- ◆ Pressing of rigid and flexible spacer types
- ◆ Two-step-pressing of insulating glass units with excessive length



Because we care

Type ZPG-R

- ◆ Type in single version
- ◆ Simultaneous assembling, gas filling and pressing of insulating glass units

Type ZPG-RTG


- ◆ Type in tandem version
- ◆ Simultaneous assembling, gas filling and pressing of two insulating glass units
- ◆ Separated press plates for tandem operation (type ZPG-RTG), single operation for oversized units

Options

- ◆ Additional equipment for gas filling with Krypton as well as gas mixtures
- ◆ Additional equipment for gas filling of triple insulating glass units
- ◆ Assembling/automatic gas filling of stepped insulating glass units (1- up to 3-sided)
- ◆ Fast reacting sensor for permanent control and monitoring of the gas filling process
- ◆ Additional device for processing of TPS® insulating glass



Rectangular format inside the press robot



Shaped format inside the press robot

Technical data	ZPG-R	ZPG-RTG
Working heights	1.60 m / 2.30 m / 2.70 m (63.0 in. / 90.6 in. / 106.3 in.)	1.60 m / 2.30 m / 2.70 m (63.0 in. / 90.6 in. / 106.3 in.)
Processable dimensions	min. 170 mm x 350 mm (6.7 in. x 13.8 in.) max. 2700 mm x 3500 mm (106.3 in. x 137.8 in.)	min. 170 mm x 350 mm (6.7 in. x 13.8 in.) max. length in tandem operation 2250 mm (65.0 in.) max. length in single operation 5000 mm (196.9 in.)
using two-step-pressing	up to max. 4500 mm (177.2 in.)	up to max. 6000 mm (236.2 in.)
Insulating glass thickness	max. 60 mm (2.36 in.)	max. 60 mm (2.36 in.)
Glass thickness	max. 15 mm (0.59 in.) (optional 30 mm [1.18 in.]	max. 15 mm (0.59 in.) (optional 30 mm [1.18 in.]



www.bystronic-glass.com
sales@bystronic-glass.com

glaston

Bystronic glass is a member
of Glaston Group
www.glaston.net