

Spacer pad applicators Types DA-VS and DA-HS

Automatic application of spacer pads on insulating glass units

- ◆ Automatically controlled application of pre-punched spacer pads on insulating glass units for contact free stacking
- ◆ No restrictions for take-off of insulating glass units due to free front surface (Type DA-HS)
- ◆ Versions with up to five application levels
- ◆ Material for application: cork, synthetic material or similar material with adhesive effects




Type DA-VS: Application on I.G. front side



Type DA-HS: Application on I.G. back side


Because we care



Type DA-VS: Exact application on I.G. front side

Exact application

- ◆ Distances of applied spacer pads:
Horizontal:
infinitely adjustable, minimum distance 100 mm
Vertical:
steady distances of application levels
- ◆ Engaged quantity of application levels depending on height of insulating glass unit
- ◆ Registration of the height for each insulating glass unit
- ◆ Also suitable for shaped formats
- ◆ Convenient and quick insertion of the roll of spacer pads into the applicator unit



Type DA-HS: Quick change of the roll of spacer pads

Option

- ◆ Increased performance due to preceded measuring device for automatically pre-setting of the application levels

Technical data	DA-VS and DA-HS
Working heights	1.60 m / 2.30 m / 2.70 m / 3.20 m (63.0 / 90.6 / 106.3 / 126.0 in.)
Processable dimensions	190 x 350 mm (7.5 x 13.8 in.) up to max. 3200 mm (126.0 in.) working height
I.G. thickness	10 – 60 mm (0.39 – 2.36 in.)
Application levels	2 – 5
Spacer pad dimensions	approx. 18 x 18 x 3 mm (0.71 x 0.71 x 0.12 in.)
Capacity of roll	approx. 16000 pcs. per roll



www.bystronic-glass.com
sales@bystronic-glass.com

glaston

Bystronic glass is a member
of Glaston Group
www.glaston.net